PATENT ABSTRACTS OF JAPAN

(11)Publication number:

11-186320

(43)Date of publication of application: 09.07.1999

(51)Int.CI.

H01L 21/60 H01L 21/3205 H01L 23/12 // H01L 21/60

(21) Application number: 10-059315

(71)Applicant: SAMSUNG ELECTRON CO LTD

(22)Date of filing:

11.03.1998

(72)Inventor: RI SHOROKU

KIM MYUNGSUNG

(30)Priority

Priority number: 97 9766918


Priority date: 09.12.1997

Priority country: KR

(54) SEMICONDUCTOR ELEMENT WITH MULTILAYERED PAD, AND MANUFACTURE THEREOF (57) Abstract:

PROBLEM TO BE SOLVED: To provide a semiconductor element provided with a multilayered pad, with which the generation of cracks can be minimized by optimizing the structure of a bonding pad, and to provide a manufacturing method of the semiconductor element.

SOLUTION: A first conductive pad 124, which extends long along one open face of the case part of a pad window region 140, is formed on the semiconductor substrate 120 provided with a first interlayer insulating film 122. A second interlayer insulating film 128, having a first via hole 126 used to expose the surface of the first conductive pad 124, is formed on the first interlayer insulating film 122, and a first conductive plug 127 is formed in the first via hole 126. A second conductive pad 130, to be connected to the first conductive plug 127, is formed on the second interlayer insulating film 128. A third interlayer insulating film 134, provided with a second via hole 132 used to expose the surface of the second conductive pad is formed, and a second conductive plug 133 is formed in



the via hole 132. A third conductive pad 136 is formed on the third interlayer insulating film 134, in such a manner that it is connected to the second conductive plug 133.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]